

## IRONWOOD CERAMIC WALL - TECHNICAL DATA

	Results	Criteria
Type	Glazed Ceramic	
Printing		
Color Variation	V1 Uniform	
Finish	Glossy	
Recycled Content	No	
Reccomended Grout Joint	3/16"	
Country of Origin	Vietnam	
Water Absorption	14-18%	EN-ISO-10545-3
DCOF	N/A	
Chemical Resistant	Yes	ASTM C650
Frost Resistant	No	
Breaking Strength	N/A	
Scratch Hardness (MOHS)	N/A	
PEI	N/A	
<b>Applications</b>		
X	commercial floors	
X	residential floors	
✓	shower wall	
X	shower floor	
X	Steam/Sauna wall	
X	Steam/Sauna floor	
X	Fireplace Surround	
X	Pool Deck	
X	Pool Waterline	
X	Pool Submerged	
X	Exterior Covered Wall	
X	Exterior Uncovered Wall	
X	Exterior Covered Floor	
X	Exterior Uncovered Floor	

## IRONWOOD CERAMIC WALL - SPECIFICATION INFO

COLORS:

SURFACE: Glossy

Available Sizes	Pieces/Box	SF/ LF per box
4x16 (color Charter only)	25	10.76
3x12	50	12.16
2x6 mud cap (color Charter only)	60	29.55 LF