OZONE CERAMIC WALL - TECHNICAL DATA

| | Results | Criteria |
|-------------------------|--------------------------|--------------------|
| Туре | Glazed Ceramic | |
| Printing | Digital Ink Jet | 22 different faces |
| Color Variation | V2 Low | |
| Finish | Matte and Glossy | |
| Recycled Content | No | |
| Reccomended Grout Joint | 3/16" | |
| Country of Origin | Spain | |
| Water Absorption | >0.16% | EN-ISO-10545-3 |
| DCOF | N/A | |
| Chemical Resistant | Yes | ASTM C650 |
| Frost Resistant | No | |
| Breaking Strength | N/A | |
| Scratch Hardness (MOHS) | N/A | |
| PEI | N/A | |
| Applications | | |
| X | commercial floors | |
| X | residential floors | |
| ✓ | shower wall | |
| X | shower floor | |
| ✓ | Steam/Sauna wall | |
| X | Steam/Sauna floor | |
| X | Fireplace Surround | |
| X | Pool Deck | |
| X | Pool Waterline | |
| X | Pool Submerged | |
| X | Exterior Covered Wall | |
| X | Exterior Uncovered Wall | |
| X | Exterior Covered Floor | |
| X | Exterior Uncovered Floor | |

OZONE CERAMIC WALL - SPECIFICATION INFO

COLORS: Snow, Greige, Coal, Mix 3D

SURFACE: Matte, Geometric 3D

| Available Sizes | Pieces/Box | SF/box | Weight/box |
|------------------------------------|------------|--------|------------|
| 10"x30"x3/8" (actual 9.84"x29.52") | 7 | 14.1 | 45.19 LBS |